

Data Sheet

Electramo NV		YE3-315L2-4 - 200kW - 1485 rpm - 400V/690V				
Industrieweg 14		IEC60034-30				
B-2390 Malle		IE3 (Premium Efficiency)				
Belgium		F / B				
+32 3 311 65 40		-20°C / +40°C				
info@electramo.com						
www.electramo.com						
BE 0414.941.452						
Electric motor Type						
Efficiencies						
Insulation class						
Temperatures						
Connection - Phases						
Tension	V	400	690	440	460	480
Frequency	Hz	50	50	60	60	60
Output	kW	200,00	200,00	240,00	240,00	240,00
Speed	min⁻¹	1.485	1485	1782	1782	1782
Current	A	334,12	193,69	364,49	348,65	334,12
Efficiency	%	100%	75%	50%		
		96,00	95,60	95,20		
Cos φ		100%	75%	50%		
		0,90	0,90	0,89		
Starting Current	A	7,10	Ia/In			
No Load Current	A	71,63	400V 50Hz			
Nominal Torque	Nm	1286,19	Nm			
Starting Torque	Nm	2,00	Ms/Mn			
Maximum Torque	Nm	2,20	Mmax/Mn			
Construction		Cast Iron				
Mounting position		B3 - IM1001 - feet - horizontal				
Protection		IP 55				
Cooling method		IC 411				
Duty type		S1				
Tropical treatment		95%				
Max. altitude A.S.L.		1000 m				
Paint (body / fan cover)		RAL 7030				
Terminal Box Position		Top - A1				
Cable entries		2 x M63x1,5 + 1 x M16x1,5				
Direction of rotation		← / →				
Drain hole(s)		Lowest point - with plug				
Bearing DE		6319 C3				
Bearing NDE		6319 C3				
Shaft dimensions	mm	80 x 170				
Oilseals DE / NDE	mm	95 x 115 x 5,5				
Balancing (Class)		Half Key				
Sound level - L(p)A	dB(A)	80,0				
Weight	Kg	1520,6				
Options & Extras		PTC				

Every care has been taken to ensure the accuracy of the information contained in this document. Due to our policy of continuous development and improvement, Electramo reserves the right to supply products which may differ from those illustrated and described in this document. Descriptions and technical features listed in this document may not be considered as binding. Under no circumstances should data in this document be considered as a contractual obligation.