



Manufacturer

VEM motors Thurm GmbH
Äußere Dresdner Str. 35
08066 ZWICKAU
Deutschland

Customer

Motoren Francoys
akkerstraat 10
MELLE
BELGIUM

**Three-phase motors with squirrel cage rotor,
Housing grey cast iron**

Type	IE3-B41R 90 L6		
Design output	(kW)	1,1	
Design torque	(Nm)	10,94	
Class IE	[-]	IE3-81%	
Efficiency determination		EN 60034-2-1	
Duty type		S1	
Design frequency	(Hz)	50	
Design speed	[rpm]	960	
Voltage	(V)	230/400	
Connection	[-]	D	Y
Current	[A]	5.01	2.88
Relative pull-in current	[-]	5,6	
Relative starting torque	[-]	2,9	
Relative pull-up torque	[-]	2,6	
Relative pull-out torque	[-]	3,4	
Efficiency100/75/50 %	[%]		81 / 81 / 77,9
Power factor	[-]	0,68	
Th. cl.		155(F/B)	
Coolant temperature	(°C)	-20°C...+40°C	
Altitude above sea level	(m)	1000m	
Degree of protection IP		IP55	
Moment of inertia	(kgm ²)	0,0075	
Motor weight	(kg)	36,2	
Bearing, D-side		6205 2Z C3	
Bearing, N-side		6205 2Z C3	
Relubrication interval	(h)		
Grease type		Asonic GLY 32	
Grease amount	(g)		
A-sound pressure level	(dB)	a.A.	
Brake type		BZFM 2,5	
Brake torque	(Nm)	27	
Relative brake torque	[-]	2,5	

Options

Type of mounting	IM B3
Flange	-
Terminal box	Standard
Position of terminal box	on the top
Cable gland	Sealing plug
Position of cable entry	right
Shaft	Standard, 1 shaft end
Bearing	Easy bearing arrangement
Limit values to vibration velocity	Class A
	Balancing with half key
Colour system	01 Moderate (KK C2),RAL 7031 blue-grey
Brake type	Stromag
Delivery conditions and/or official regulations:	IEC / EN 60034-1

This document was produced electronically, all specifications are valid only after confirmation of the manufacturer

Data sheet


14.01.2020 MADE WITH VEM EKAT V10.9



Three-phase motors with squirrel cage rotor,
Housing grey cast iron


IE3-B41R 90 L6

Mounting position



Type of mounting: IM B3
Flange: -
Position of terminal box: on the top
Brake type: BZFM 2,5
Forced-ventilation:

Terminal box: KA 05
Cable gland O: 1 x Sealing plug



Motor

A	AA	AB	AC	AD	B	B'	BA	BA'	BB	C	CA	K	K'
140	40	178	177	-	125	-	-	-	155	56	-	10	10
L	LC	H	HA	HD	HH	BI	Protection cover			Terminal box			
412	-	90	10,5	217	75	18	L	AG	LL	BE	AH	-	-
								92	92	-	-		

Flange

P	N	LA	M	T	S	Tolerances			
-	-	-	-	-	-	H	N	D	DA
						-0,5	j6	k6	k6

Shaft-DS

D	E	GA	F	DB
24	50	27	8	DIN 332 DS - M8

Shaft-NS

DA	EA	GC	FA
-	-	-	-

DB...Centre hole

Delivery conditions and/or official regulations: IEC / EN 60034-1

This document was produced electronically, all specifications are valid only after confirmation of the manufacturer